

WEATHERGUARD SITE TRIPOD

SITE TRIPOD HEADS & TRIPOD

Quick and easy to deploy, Weatherguard Site tripod mounted fittings offer ultimate flexibility on site. The heads are supplied ready to mount onto the tripod, complete with 2x110V power outlets and 5m of cable.





Features

- Fast and easy to set up on site
- Heads fitted with twin 110V sockets
- Pre-wired with 5m cable and plug
- Separate, height adjustable tripod



Specification

Code	Description	Lumen Output	Emergency Lumen Output	Wattage	Efficacy
WGS/TP	Weatherguard Site Adjustable Tripod				

Product Information

IP Rating	IP65
IK Rating	IK07
Material (Body/Housing)	Steel

Colour Rendition (CRI)	Ra > 80
Approval	UKCA & CE

Tel: 0114 279 8999 | E

Email: sales@redarrowelectrical.co.uk

redarrowelectrical.co.uk




WEATHERGUARD SITE TRIPOD

SITE TRIPOD HEADS & TRIPOD

Packaging Information

Dimensions (mm)	L: 1280 x W: 1050 mm	
Product Net Weight (kg)	3.7 kg	
Barcode	5055807622783	

Box Dimensions (mm)	L: 1340 x W: 180 x D: 175 mm	
Box Gross Weight (kg)	4.25 kg	



el: 0114 279 8999 | Email: sales@redarrowelectrical.co.uk | redarrowelectrical.co.u