

Knightsbridge


DATASHEET



VFRIC8CW

230V IP65 8W Fire-Rated Valknight LED Downlight 4000K

www.mlaccessories.co.uk



MLA PART CODE	VFRIC8CW
DESCRIPTION	230V IP65 8W Fire-Rated Valknight LED Downlight 4000K
NET WEIGHT (KG)	0.2715
DIFFUSER	Clear
DIMENSIONS (MM)	Diameter - 80 Projection - 4 Recessed Depth - 50 Recessed Depth with IC Cage - 90 Minimum Void - 100
CUT-OUT (MM)	Cut-out Diameter - 65
CONSTRUCTION	Construction - Die-cast aluminium
CLASS	II
IP RATING	IP65 (IP20 from above)
WATTAGE (W)	8
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	640
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	73.52
CIRCUIT WATTAGE (W)	8.677
CCT	4000K
LIGHT COLOUR	Cool White
CRI	>80
SDCM	<6
RUNNING CURRENT (A)	0.04182
BEAM ANGLE (DEGREES)	40
LIFE SPAN (HRS)	25,000
DIMMABLE	Yes*
EMERGENCY CONVERSION KIT	VFR7EM
FIRE-RATED	Tested to 30/60/90 minutes



ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.





I-JOIST RATED	30 minutes
IC RATED	With IC cage only
INPUT VOLTAGE	230V 50Hz
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 8W OUTPUT VOLTAGE - 25-36V OUTPUT CURRENT - 240mA POWER FACTOR - >0.9 AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 85°C
WARRANTY	5year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	<u>5055832943402</u>

Date Created: 08/11/2023 12:10



ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.

