

Product selected: Lynx-S 9W 840

An energy efficient compact fluorescent lamp comprising a U shaped tube and a 2 pin base which incorporates the starter and capacitor.
For use with a remote magnetic ballast

Applications	Features	Directions for use
<ul style="list-style-type: none"> - Can replace standard incandescent lamps providing a suitable lampholder/ luminaire is used - Suitable for commercial and domestic applications 	<ul style="list-style-type: none"> - Use considerably less power and last up to 10 times longer than incandescent lamps - Wattages: 5W, 7W, 9W and 11W - Excellent colour rendering (Ra85/ Class1B) - Available in colours: Homelight Deluxe 827, Warmwhite Deluxe 830, White Deluxe 835, Coolwhite Deluxe 840 and Daylight Deluxe 860 - 2-pin G23 cap with integral starter - Average rated life: 10000 hours 	<ul style="list-style-type: none"> - For use with remote magnetic ballast - Lynx-S lamps are not suitable for operation on dimmer circuits

Product Attributes

Item description	Lynx-S 9W 840
Nominal wattage (W)	9
Cap	G23
Mercury content per lamp [mg]	4.6
Colour rendering Index - CRI (class / %)	/82
Colour temperature (K)	4000
Nominal luminous flux at 25°C (lm)	600
Lumen maintenance min. 2000 h (50 Hz)	0.92
Lumen maintenance min. 4000 h (50 Hz)	0.88
Lumen maintenance min. 6000 h (50 Hz)	0.85
Lumen maintenance min. 8000 h (50 Hz)	0.82
Lumen maintenance min. 12000 h (50 Hz)	0.8
Ambient temperature for max. lumen flux (°C)	25
Rated luminous flux at 25°C (lm)	600
Nominal average life (h)	10000
Survival factor 2000 h (50 Hz)	0.98
Survival factor 4000 h (50 Hz)	0.95
Survival factor 6000 h (50 Hz)	0.9
Survival factor 8000 h (50 Hz)	0.85
Survival factor 12000 h (50 Hz)	0.62
Packing Quantity	10
EAN Code	5410288258904
Ordering Code	0025890

Product Image